

**ARDON®**

TECHNICAL DATA SHEET

G5000


Eye protection

Article NO: E4040


Lens: clear
Material- lens: polycarbonate
Material- frame: polypropylene
Material- face sealing: AES Santropene



Stylish enclosed safety goggles with polypropylene black and grey frame and 25-mm long adjustable rubber band. Grey face sealing is made of AES Santropene, a thermoplastic material with very high aging resistance. Polycarbonate lens are easily replaceable and they are 2 mm thick. Clear polycarbonate lens are made from one piece, protect against UV radiation, are resistant to medium-energy shocks (up to 120 m/s) at extreme temperatures (-5 °C - +55 °C). Provides maximum protection and unusually big field of view. Top-quality goggles providing maximum protection and comfort because of indirect aeration system.



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

Clear lens, UV, 1 BT 9 0

Type of the filter:

UV filter

Shade number:

clear lens

Optical class:

1

permanent use

Mechanical resistance:

BT

resistant to medium-energy shocks at extreme temperatures

Suitable use:

9

molten metal and hot solid substances

Type of the lens:

0

original lens

ARDON SAFETY s. r. o.

Tržní 2902/14, Přerov I - Město
Tel.: 581 250 061 www.ardon.cz



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands),
Certificate no CE 749754, dated 26th August 2021.

Pieces in carton:	120
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	17 kg
Carton size:	0,089 m ³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
