



ARDON®
WORKWEAR
& OUTDOOR

NITRAX BASIC

HANDLING IN SLIGHTLY OILY ENVIRONMENT



EN 388: 2016

TECHNICAL DATA



ARDON®
WORKWEAR
& OUTDOOR

NITRAX BASIC

HANDLING IN SLIGHTLY OILY ENVIRONMENT

CODE

A9054

MATERIAL

Lining 13G polyester (white)
Coating nitrile (grey)
Thickness 1,1 mm (in palm)

SIZE(S):

7 / S – 11 / 2XL

UNIT

pair

PACKING

Units in carton 240 pairs
Units in polybag 12 pairs
Retail packing size 10 / XL also with sales label (10/SPE)

DIMENSIONS


Carton H x W x D (cm)
Carton (cbm)

5	6	7	8	9	10	11	12
-	-	46x25x45	46x25x45	46x25x45	46x25x45	46x25x45	-
-	-	0,0518	0,0518	0,0518	0,0518	0,0518	-

WEIGHT

Carton (kg)
Unit (g)

5	6	7	8	9	10	11	12
-	-	9,00	9,10	9,30	10,5	11,3	-
-	-	37,5	38,0	38,5	43,0	47,0	-



Size chart (cm)

Total length (A)
Cuff length (B)
Cuff width (C)
Palm width (D)

5	6	7	8	9	10	11	12
-	-	23,0	24,0	25,0	26,0	27,0	-
-	-	7,00	7,00	7,50	8,00	8,50	-
-	-	7,00	7,20	7,55	8,00	8,50	-
-	-	9,50	10,0	10,5	10,7	10,8	-

Tolerance (A) $\pm 0,50$ (cm)
Tolerance (B) $\pm 0,30$ (cm)

Tolerance (C) $\pm 0,30$ (cm)
Tolerance (D) $\pm 0,30$ (cm)

DESCRIPTION

Fine polyester knitted fabric dipped in nitrile.

TECHNICAL DATA

STANDARDS

(EU) 2016/425

EN ISO 21420:2020 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks

EN 388



PROTECTION LEVELS

MECHANICAL RISKS

abrasion resistance
cut resistance
tearing resistance
puncture resistance
cut resistance acc. to ISO

LVL

4
1
3
1
X

score

> 8.000
1,2 – 2,5
50 – 75
20 – 60
not measured

unit

cycles
index
N
N
N

SPECIAL FEATURES

- half-dipped gloves
- Size 10 also available in retail packaging ('retail ready')



ARDON®
WORKWEAR
& OUTDOOR

Basic packaging (without sales label)

A9054/07

A9054/08

A9054/09

A9054/10

A9054/11

Retail packaging (with sales label)

A9054/10/SPE

EAN

8592390017987

8592390017994

8592390018007

8592390018014

8592390018021

8592390081377

HEM COLOR

red

yellow

brown

black

green

black

