



TECHNICAL DATA SHEET

AS-5

Combined protection



Article NO: D1004

Material: HDPE
Colour: white, red, blue, orange,
green, yellow

Safety helmet, special designed for ultimate comfort with ventilation, wheel ratchet, sweat band, 6 point webbing harness, great stability.
Service life: 5 years. Heat resistant from -20°C to +50°C.

Accessories:

AS-5-2	chin-strap for helmet AS-5
AS-5-3	sweat band from faux leather
AS-5-4	6 point webbing harness with ratchet

This personal protective equipment is in conformity with these harmonized European Standards:

EN 397+A1:2012 : Industrial safety helmets.

Certified by notified body no. 1024 (Výzkumný ústav bezpečnosti práce, v. v. i., Jeruzalémská 1283/9, 110 00, Praha 1, Czech republic),
Certificate number 1024/E-063/2022, dated 5th May 2022.



Pieces in carton:	20
Polybag packing (pieces):	1
Carton weight:	10 kg
Carton size:	0,142 m ³

To provide protection this helmet must be adjusted to the size of the user's head. To alter the fit, adjust the wheel ratchet at the back of the helmet. The outer shell of the helmet is to be cleaned with warm water using a small amount of detergent. Direct contact with liquids containing organic solvents or alcohol may reduce the mechanical strength of the shell and therefore such contact must be avoided. Six-point webbing harnesses are to be cleaned with a lukewarm weak solution of water and detergent, rinsed well and left to dry. The sweatband is to be cleaned with a disinfecting and cleaning agent, if heavily soiled we recommend replacing the sweatband. For long term storage as well as transportation we recommend using the original container of the helmet. Before each use of the helmet, it is necessary to inspect it thoroughly to establish whether it is cracked, cut or damaged in a different way.
