



ARDON®
WORKWEAR
& OUTDOOR

ARDON® EBON O2

WORKING SHOES



DRY AIR



WASH-FRIENDLY



NONMETALLIC



ARDON®
WORKWEAR
& OUTDOOR

ARDON® EBON O2

WORKING SHOES

ARTICLE

G3360

MATERIAL

Upper MICROFIBER with a thickness of 1,4 mm
Lining MESH laminated breathable fabric
Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip
Toe cap -
Plate -
Insole ANATOMIC GEL – anatomically shaped PU foam with cushioning gel in the heel area

SIZE

36-48

UNIT

PACKAGE

Units in a carton
Units in a box

10 pairs
1 pair

DIMENSIONS

	36-41	42-48
Carton H x W x D (cm)	59 x 34 x 40,5	61,5x 36 x 41,5
Carton (cbm)	0,0812	0,0919

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	235	241	248	255	262	270	276	283	290	297	304	310	317	-	-	-
Foot length cm	-	23,0	23,6	24,3	25,0	25,7	26,5	27,1	28,3	28,5	29,2	29,9	30,5	31,2	-	-	-

DESCRIPTION

Black low shoe is ideal not only for the hospitality industry. The upper is made of microfiber that is washing machine safe up to 30°C. For greater comfort, the shoes were designed with an anatomically shaped insole with a gel component that absorbs shocks during walking and lowers the impact on the heel area. The lightweight dual-density polyurethane outsole meets SRC slip resistance requirements.

NORMS

(EU) 2016/425

EN ISO 20347:2012















Personal protective equipment - Occupational footwear

Category

O2 SRC

Categories

EN ISO 20347

E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3360/36	8592390150554	9.6	0.96
G3360/37	8592390150561	9.8	0.98
G3360/38	8592390150578	10,0	1,00
G3360/39	8592390150585	10.2	1.02
G3360/40	8592390150592	10.4	1.04
G3360/41	8592390150608	10.6	1.06
G3360/42	8592390150615	10.8	1.08
G3360/43	8592390150622	11,0	1.1
G3360/44	8592390150639	11.2	1.12
G3360/45	8592390150646	11.4	1.14
G3360/46	8592390150653	11.6	1.16
G3360/47	8592390150660	11.8	1.18
G3360/48	8592390150677	12,0	1.20



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

