



ARDON®
WORKWEAR
& OUTDOOR

ARDON® FLYTEX S1P

SAFETY SHOES



DRY AIR



DEFUSE
CONTROL



WASH-FRIENDLY

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® FLYTEX S1P

SAFETY SHOES

ARTICLE

G3353

G3387

COLOUR MATERIAL

Upper
Lining
Sole
Toe cap
Plate
Insole

black

grey

3D KNIT type knitted two-layer fabric

MESH laminated breathable fabric

PU/PU, two-component spray coating, oil resistant, anti-static, antislip

steel 604

steel

ANATOMIC GEL - anatomically shaped from PU foam with a gel cushioning in the heel area

SIZE

34-51

35-50

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D
(cm)

34-41

57x 33 x 38,5

42-45

59,5x 35,5 x 40,5

46-51

62x38x41,5

Carton (cbm)

0,0724

0,0855

0,0978

Size EUR	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	222	228	235	241	248	255	262	270	276	283	290	297	304	310	317	323	330	337
Foot length cm	21,7	22,3	23,0	23,6	24,3	25,0	25,7	26,5	27,1	28,3	28,5	29,2	29,9	30,5	31,2	31,8	32,5	33,2

DESCRIPTION

Safety shoe with a sporty design, fits perfectly on the foot thanks to the upper made of the seamless 3D KNIT technology. The knitted upper consists of two layers of textile in a contrasting color design. Reinforced with offset printing in the area of the toe and around the laces. The breathability of the shoes is ensured by the laminated MESH fabric in the area of the lining and the tongue. The ANATOMIC GEL insole with a cushioning gel element in the heel takes care of the comfort of the shoes. The stable polyurethane sole made by direct spraying provides the highest level of anti-slip properties.

NORMS















(EU) 2016/425

EN ISO 20345:2011

Category

Personal protective equipment – Safety footwear

S1P SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3353/34	8592390359759	10,1	1,01
G3353/35	8592390126719	10.6	1.06
G3353/36	8592390126726	10.8	1.08
G3353/37	8592390126733	11.1	1.11
G3353/38	8592390126740	11.5	1.15
G3353/39	8592390126757	11.8	1.18
G3353/40	8592390126764	12.2	1.22
G3353/41	8592390126771	12.6	1.26
G3353/42	8592390126788	13.1	1.31
G3353/43	8592390126795	13.8	1.38
G3353/44	8592390126801	14.2	1.42
G3353/45	8592390126818	14.5	1.45
G3353/46	8592390126825	15.1	1.51
G3353/47	8592390126832	15.3	1.53
G3353/48	8592390126849	15.7	1.57
G3353/49	8592390126856	16.3	1.63
G3353/50	8592390126863	16.8	1.68
G3353/51	8592390359766	17.2	1.72
G3387/35	8592390153593	10.6	1.06
G3387/36	8592390153609	10.8	1.08
G3387/37	8592390153616	11.1	1.11
G3387/38	8592390153623	11.5	1.15
G3387/39	8592390153630	11.8	1.18
G3387/40	8592390153647	12.2	1.22
G3387/41	8592390153654	12.6	1.26
G3387/42	8592390153661	13.1	1.31
G3387/43	8592390153678	13.8	1.38
G3387/44	8592390153685	14.2	1.42
G3387/45	8592390153692	14.5	1.45
G3387/46	8592390153708	15.1	1.51
G3387/47	8592390153715	15.3	1.53
G3387/48	8592390153722	15.7	1.57
G3387/49	8592390153739	16.3	1.63
G3387/50	8592390153746	16.8	1.68



ARDON®

**WORKWEAR
& OUTDOOR**





ARDON®
WORKWEAR
& OUTDOOR

