



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## ARDON® PROOF CUT 4C

HANDLING IN DRY ENVIRONMENT WITH HIGH CUT PROTECTION  
AND STATIC PROTECTION



EN 388: 2016



EN 16350

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

# ARDON® PROOF CUT 4C

HANDLING IN DRY ENVIRONMENT WITH HIGH CUT PROTECTION  
AND STATIC PROTECTION

## CODE

A5021

## MATERIAL

Lining

15G HPPE (High Performance Polyethylene) + Carbon Fiber  
+ Spandex

Thickness

1,0 ± 0,2 mm (in palm)

## SIZE(S):

6 / XS – 9 / L

## UNIT

pair

## PACKING

Units in carton

120 pairs

Units in polybag

12 pairs

Retail packaging

N/A

## DIMENSIONS

Carton H x W x D (cm)

Carton (cbm)


| 5 | 6        | 7        | 8        | 9        | 10 | 11 | 12 |
|---|----------|----------|----------|----------|----|----|----|
| - | 48x24x20 | 48x24x20 | 48x24x20 | 48x24x20 | -  | -  | -  |
| - | 0,023    | 0,023    | 0,023    | 0,023    | -  | -  | -  |

## WEIGHT

Carton (kg)

Unit (g)

| 5 | 6    | 7    | 8    | 9    | 10 | 11 | 12 |
|---|------|------|------|------|----|----|----|
| - | 2,90 | 3,00 | 3,11 | 3,30 | -  | -  | -  |
| - | 15,6 | 16,3 | 17,0 | 19,7 | -  | -  | -  |



## Size chart (cm)

Total length (A)

Cuff length (B)

Cuff width (C)

Palm width (D)

| 5 | 6    | 7    | 8    | 9    | 10 | 11 | 12 |
|---|------|------|------|------|----|----|----|
| - | 21,0 | 22,0 | 23,0 | 24,0 | -  | -  | -  |
| - | 6,00 | 6,20 | 6,50 | 6,80 | -  | -  | -  |
| - | 8,20 | 8,50 | 8,80 | 9,00 | -  | -  | -  |
| - | 9,00 | 9,30 | 9,50 | 10,0 | -  | -  | -  |

Tolerance (A) ± 0,50 (cm)

Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)

Tolerance (D) ± 0,70 (cm)

## DESCRIPTION

Highly durable ESD cut-resistant knit without dipping.


TECHNICAL DATA

## STANDARDS

(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks

|  | PROTECTION LEVELS          |            |               |
|---|----------------------------|------------|---------------|
|   | <b>MECHANICAL RISKS</b>    |            |               |
|   | abrasion resistance        | <b>LVL</b> | <b>score</b>  |
|   | cut resistance             | 3          | 2.000 – 8.000 |
|   | tearing resistance         | 4          | 10 - 20       |
|   | puncture resistance        | 4          | > 75          |
|   | cut resistance acc. to ISO | X          | not measured  |
|   |                            | C          | 10 - 15       |
|   |                            |            | <b>unit</b>   |
|   |                            |            | cycles        |
|   |                            |            | index         |
|   |                            |            | N             |
|   |                            |            | N             |
|   |                            |            | N             |

**EN 16350:2014**

Protective gloves - general requirements and test methods  
for antistatic properties



### SPECIAL FEATURES

- ESD cut resistant gloves
- durable knit (4C cut resistance)
- ARDON® design:
  - mandatory information on inner label
  - reflective manufacturer's logo
- do not leave fingerprints
- compatible with touch screens
- also available with polyurethane fingertips dipping = LEO CUT 4C
- also available with polyurethane palm dipping = BUCK CUT 4C



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

**Basic packaging (without sales label)**

A5021/06  
A5021/07  
A5021/08  
A5021/09

**EAN**

8592390180971  
8592390180988  
8592390180995  
8592390181008

**HEM COLOR**

violet  
yellow  
green  
orange

