



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® PURE X

SAFETY SPECTACLES



UV FILTER



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® PURE X

SAFETY SPECTACLES

**ARTIKLE NO.**

**E4297 (Clear)**

**MATERIAL lens**  
**MATERIAL temples**  
**LENS**

polycarbonate  
polycarbonate  
Clear

## DESCRIPTION

Comfortable and versatile protective glasses with a modern and sporty design offer combination of safety, comfort, and versatility. Thanks to their shape, they are suitable for both work and leisure activities. Adjustable nose bridge for greater comfort. Rubberized and non-slip temple tips ensure that the glasses fit perfectly during any activity. The lenses offer anti-scratch and anti-fog Protection. UV Protection up to 400 nm.

## STANDARDS






This personal protective equipment is in conformity with these harmonized European Standards.

**EN ISO 16321-1:2021:** Eye and face protection for occupational use.

**EN 166:2001:** Personal eye protection - Specifications

Certification have been performed on the base of technical documentation of the PPE and practical exams of the ergonomic features of the PPE by the Ardon s.r.o. company, from 1th of July 2024, test report No. TR-2407104.

### Lens Clear, UV 400, AR UL1,2 1 CT

Type of filter	UL	UV filter
Shade number	1.2	Clear
Optical class	1	pernament use
Mechanical resistance	CT	Resistance to surface damage by fine particles (F) and protection against high speed particles at extreme temperatures - 5°/+55° C (T).
Adjustment of temples in lenght	x	
Adjustment of temples in inclination	x	
Anti-fog lens	✓	
Anti-scratch lens	✓	
UV	✓	



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>PIECES IN CARTON</b>	300 pcs
<b>PIECES IN A BOX</b>	10 pcs
<b>WEIGHT OF A CARTON</b>	17kg
<b>SIZE OF A CARTON</b>	0,171 m <sup>3</sup>
<b>UNIT PACKING (POLYBAG)</b>	1 pc

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents. It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

